

Application No. 10/724,184
Amendment dated October 4, 2004
Page 2

Amendments to the Claims:

The following claims will replace all prior versions of the claims in this application (in the unlikely event that no claims follow herein, the previously pending claims will remain):

1. (Currently amended) A gasket ~~in the form of~~ comprising a frame having an inner peripheral edge and an outer peripheral edge, the inner peripheral edge ~~of the gasket~~ being convex and of continuously curved convex configuration over the full width of the gasket and being provided with a liner of chemically resistant material conforming with the convex and continuously curved inner peripheral edge.
2. (Original) A gasket as claimed in Claim 1, in which the liner is made of polytetrafluoroethylene.
3. (Original) A gasket as claimed in Claim 1, in which the inner peripheral edge is part-circular in cross-section.
4. (Original) A gasket as claimed in Claim 1 provided with holes to accommodate sealing bolts.
- 5-6. (Cancelled).
7. (Original) A gasket as claimed in Claim 1 in which the opposite faces of the gasket are planar.
8. (Currently amended) A gasket ~~comprising in the form of~~ a frame having an inner peripheral edge and an outer peripheral edge and including a protrusion or nose at its inner and/or outer peripheral edge, the protrusion or nose being convex and of continuously curved configuration over the full width of the gasket and being provided with a liner of chemically resistant material conforming with the convex and continuously cured inner peripheral edge.

Application No. 10/724,184
Amendment dated October 4, 2004
Page 3

9. (Original) A gasket as claimed in Claim 8, in which the protrusion or nose extends around substantially the entire perimetral length of the frame.
10. (Original) A gasket as claimed in Claim 8, which the protrusion or nose is provided on the inner peripheral edge of the gasket frame.
11. (Cancelled).
12. (Original) A gasket as claimed in Claim 10, in which the protrusion or nose is of curved bulbous configuration.
13. (Original) A gasket as claimed in Claim 10, further including a liner of chemically resistant material provided on said inner peripheral edge and conforming to the configuration of the nose.
14. (Original) A gasket as claimed in Claim 13, in which the liner is made of polytetrafluoroethylene.
15. (Original) A gasket as claimed in Claim 8 in which the protrusion or nose is of a shape capable of effecting a pinch seal when used with a second gasket in the form of a frame having an inner peripheral edge and an outer peripheral edge, the inner peripheral edge of the gasket being of continuously curved convex configuration and being provided with a liner of chemically resistant material conforming with the continuously curved inner peripheral edge.
16. (Original) A gasket as claimed in Claim 8 in which the gasket is provided with a protrusion or nose on opposite sides thereof.
17. (Original) A gasket as claimed in Claim 8 in which the frame is locally enlarged at its inner peripheral edge to form said nose which projects beyond the plane of the gasket on one side thereof to effect sealing contact.

Application No. 10/724,184
Amendment dated October 4, 2004
Page 4

18. (Original) A gasket as claimed in Claim 8 wherein said comprising a frame is suitable for compression together with the frame of a second gasket of similar configuration between a pair of flanges, the protrusion being resilient for effecting a pinch seal with a similar protrusion on a second gasket.
19. (Currently amended) A gasket effective for compression together with ~~the~~ a frame of a second gasket of similar configuration between a pair of flanges, ~~the gasket comprising~~ a frame having a resilient protrusion on one side thereof for effecting a pinch seal with a similar protrusion on a second gasket, the resilient protrusion being located at or adjacent the inner periphery of the frame and remote from the outer periphery of the frame, said protrusion being convex and of continuously curved configuration over the full width of the gasket and being provided with a liner of chemically resistant material conforming with the convex and continuously curved inner peripheral edge, and in which the inner periphery of the gasket is protected by a chemically resistant liner which extends over the protrusion.
20. (Currently amended) A gasket as claimed in claim 20, wherein the chemically resistant resistant liner comprises polytetrafluoroethylene.
21. (New) A gasket comprising a square or rectangular frame having an inner peripheral edge and an outer peripheral edge, the inner peripheral edge of the gasket being of continuously curved convex configuration and being provided with a liner of chemically resistant material conforming with the continuously curved inner peripheral edge.
22. (New) The gasket of claim 21 wherein the cross-section of the frame is of rectangular cross section with the dimension perpendicular to the gasket plane being smaller than the dimension in the plane of the gasket.
23. (New) The gasket of claim 1 wherein said liner is of substantially uniform thickness.
24. (New) The gasket of claim 8 wherein said liner is of substantially uniform thickness.

Application No. 10/724,184
Amendment dated October 4, 2004
Page 5

25. (New) The gasket of claim 19 wherein said liner is of substantially uniform thickness.